

DOCUCUTTER HC-6801 SPECIFICATIONS

Maximum Cutting Width	26.8" (680 mm)		
Minimum Cut	0.60" (15.2 mm) without false clamp 2.0" (25.4 mm) with false clamp		
Maximum Cutting Depth	27.2″ (691 mm)		
Clamp Opening	4.0″ (101.5 mm) without false clamp 3.8″ (96.5 mm) with false clamp		
Clamping Method	Adjustable hydraulic		
Maximum Clamping Pressure	2,500 lb. (1134 kg/cm2)		
Minimum Clamping Pressure	556 lb. (252 kg)		
Backgauge Control	Power with micro adjustment		
Backgauge Speed	4.0"/second (100 mm/second)		
Table Space	18.9″ (480 mm) in front of knife 36.9″ (937 mm) behind knife		
Overall Height	59.8″ (1,520 mm)		
Option Knife Steel	Tungsten Carbide		
Approx. Net Weight	1,202 lb. (545kg)		
Power Requirements	Single phase, 200-240VAC, 50/60Hz, Max 16A		
Safety Certification	ETL, CETL		
Hydraulic Motor	2HP(IE3) with inverter, single phase, 50/60Hz, 15.7A		

Production rates are based on optimal conditions and may vary depending on stock and enviromental conditions.



Duplo The leading provider of innovative precision finishing, print embellishment, and specialty finishing solutions. Contact us today to request samples or to get in touch with a finishing specialist.

Duplo USA Corporation

3050 S. Daimler St. Santa Ana, California 92705 Toll Free: 1-800-255-1933 Telephone: 1-949-752-8222 Email: sales@duplousa.com

Find Us Online



linkedin.com/company/duplo-usa-corporation facebook.com/duplousa twitter.com/duplousa youtube.com/duplousa

©2020 Duplo USA Corporation. All rights reserved. The information contained herein is subject to change without notice and products may be shown with optional features. Duplo shall not be liable for any errors or omissions contained in this document.

Duplo

HC-680i Hydraulic Cutter

Programmable, High Pile Cutting for Wider Form

DocuCutter HC-680i Hydraulic Cutter

The programmable HC-680i Hydraulic Cutter effortlessly cuts through large stacks of paper up to 26.8" wide. Trim high volume jobs faster and with accurate performance. Finish stacks of postcards, direct mail, and perfect bound books up to 4.0" in height. With its cast iron construction and intelligent software, the HC-680i offers a safe and productive solution for your paper cutting needs.



The HC-680i makes paper cutting a quick and easy task. Program the cuts and sequence for each job using the 10.4" touchscreen control panel and intuitive software. Store up to 999 jobs in memory with up to 128 cuts each to recall when needed. Or program your job offline and save it in .csv format to upload via USB. As each cut is performed, the backgauge automatically adjusts for the next cut and the control panel prompts the cut rotation to eliminate errors and increase efficiency. Simply rotate the job and discard the scraps. You can also set each cut and position the backgauge using the fine-tuning knob as you go.

The HC-680i is barcode-ready to instantly retrieve any pre-programmed job simply by scanning the printed barcode. Ideal for running multiple jobs in faster turnarounds, the barcode reader saves time by setting up the machine with all commands in place.




Once the job has been programmed, place the pile on the table and slide it against the backgauge. The LED light illuminates the cutting line allowing you to see exactly where the cut will be applied. The foot pedal controls the low-pressure clamp, which keeps the job firmly in place to prevent it from fanning and removes any excess air between the sheets. Press the dual palm buttons to release the blade and observe as each cut is performed with accuracy.

With a touch of a button, the push-out function automatically pushes the paper stack forward as needed. The HC-680i is built to last and features adjustable clamp pressure, enclosed rear table, and an aluminum alloy work table with a low friction surface.

APPLICATIONS



Hydraulic-powered clamping and cutting



The HC-680i comes with a barcode scanner that can be used to load any pre-programmed job by reading the barcode.

HC-680i



PROGRAMMABLE, INTUITIVE SOFTWARE

Main Menu			Prog	Cut	Help	
сит	SIZE	PUSH	ROTATE	JOB	JOB NAME	
1	18.000		C CW 90*	10		
2	12.000		C CW 180*			
3	11.000		C CW 90*			
4	8.500) ccw 99*	_	11.000	inc
5	5.000) ccw 99"			
6						-
7				Balagaros	1	Run
8						P
P	AGE UP		GE DN	E		REVER
				DEL	ETE	CLEAF

After each cut is completed, the touchscreen control panel will prompt you in which direction to rotate the stack to prevent cutting errors.





OPERATOR SAFETY

When it comes to guillotine cutting, your protection is top priority and the HC-680i meets safety standards with ETL approval. Sensors on both ends of the table guard hands and ensure the cutting area remains clear during operation. The dual palm buttons activate the sensors and beam a Category 4 safety light curtain that disables the clamp and the blade when an object comes too close.

For an added level of safety, the cutter hydraulic leak protection prevents the knife from being released in the case of an oil leakage.

FEATURES

- Paper cutting up to 26.8" wide
- Programmable backgauge control
- Linux operating system
- Dual palm cut buttons
- Barcode capabilities
- · Safety light curtain